

Data Sheet

FUJITSU Tablet STYLISTIC R726

Unlimited Usability and Productivity with 2 in 1

The FUJITSU Tablet STYLISTIC R726 with a 31.8 cm (12.5-inch) anti-glare display transforms into a full performance and full productivity notebook by simply attaching the slim Magnetic Keyboard. Its magnesium-aluminum housing delivers durability for business pros on the move, presenting in tablet mode or working in notebook mode on a plane, a train or anywhere else. You can use a digital pen to take notes or even signatures on the tablet. Enterprise-grade connectivity like 4G/LTE and security features like encrypted drives and NFC-based authentication allow you to do your job wherever you want; all in confidence that your data is secure.

Powerful and responsive 2 in 1

Business tablet, business notebook, one device

- Transform a tablet into a full-fledged notebook by simply attaching the Magnetic Keyboard and unfolding the integrated Tablet Stand

Mobility first

Smart features for dynamic work styles

- Anti-glare display option, durable yet thin & light magnesium-aluminum housing, flexible input options, UC&C capabilities, long runtime of up to 12 hours

Go-anywhere connectivity

Smart features let you do your job wherever you want

- Optional embedded 4G/LTE, NFC and Intel® Pro Wireless Display functionality

Enterprise-grade manageability and security

Future-proof security features and remote management capabilities keep data safe

- Embedded NFC for contactless SmartCard authentication, encrypted drives and TPM

Best-in-class office comfort

Switch to a full desktop-like experience in no time

- Cradle to attach peripherals in the office



Components

Base unit	STYLISTIC R726 i3/4GB/non-vPro	STYLISTIC R726 i5/4GB/non-vPro	STYLISTIC R726 i5/8GB/VPro	STYLISTIC R726 i7/8GB/VPro
Operating systems				
Operating system	Windows 10 Pro	Windows 10 Pro	Windows 10 Pro	Windows 10 Pro
Operating system compatible	Windows 8.1	Windows 8.1	Windows 8.1	Windows 8.1
Hard disk drives (internal)				
	SSD SATA III, 512 GB, M.2 module, OPAL capable			
	SSD SATA III, 256 GB, M.2 module, OPAL capable			
	SSD SATA III, 128 GB, M.2 module, OPAL capable			
Hard disk notes	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software. Up to 20 GB of HDD space is reserved for system recovery Internal storage interface: M.2 SATA			
Interface add on cards/components (optional)				
Multimedia				
Camera	Front camera 2 megapixel, rear camera 5 megapixel with autofocus			

Base unit

Base unit	STYLISTIC R726 i3/4GB/non-vPro	STYLISTIC R726 i5/4GB/non-vPro	STYLISTIC R726 i5/8GB/VPro	STYLISTIC R726 i7/8GB/VPro
General system information				
Processor	Intel® Core™ i3-6100U processor	Intel® Core™ i5-6200U processor	Intel® Core™ i5-6300U processor	Intel® Core™ i7-6600U processor
	(2 Cores / 4 Threads, 2.3 GHz)	(2 Cores / 4 Threads, 2.3 GHz, up to 2.8 GHz)	(2 Cores / 4 Threads, 2.4 GHz, up to 3.0 GHz)	(2 Cores / 4 Threads, 2.6 GHz, up to 3.4 GHz)
Chipset	Integrated in CPU	Integrated in CPU	Integrated in CPU	Integrated in CPU
Chipset notes	- - -	- - -	Supports iAMT 11.0 Intel® vPro™ requires Core i5-63xx & i7-66xx CPU, Intel WLAN 8260ac, TPM module	Supports iAMT 11.0 Intel® vPro™ requires Core i5-63xx & i7-66xx CPU, Intel WLAN 8260ac, TPM module
Supported capacity RAM	4 GB	4 GB	8 GB	8 GB
Memory slots	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)	LPDDR3 (1600 MHz)
LAN	Built-in 10/100/1,000 MBit/s Intel® I219V	Built-in 10/100/1,000 MBit/s Intel® I219V	Built-in 10/100/1,000 MBit/s Intel® I219LM	Built-in 10/100/1,000 MBit/s Intel® I219LM
LAN notes	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable	LAN connector via optional cradle or optional USB adapter cable
BIOS features	InsydeH20 Bios	InsydeH20 Bios	InsydeH20 Bios	InsydeH20 Bios
Audio type	On board	On board	On board	On board
Audio codec	Realtek ALC255	Realtek ALC255	Realtek ALC255	Realtek ALC255
Audio features	2x digital array microphones, 2x built-in speakers (stereo)	2x digital array microphones, 2x built-in speakers (stereo)	2x digital array microphones, 2x built-in speakers (stereo)	2x digital array microphones, 2x built-in speakers (stereo)

Display				
Display	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Glare or anti-glare display,1,920 x 1,080 pixel,700:1,400 cd	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Glare or anti-glare display,1,920 x 1,080 pixel,700:1,400 cd	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Glare or anti-glare display,1,920 x 1,080 pixel,700:1,400 cd	31.8 cm (12.5-inch),PLS (Plane to Line Switching),(Full HD),Glare or anti-glare display,1,920 x 1,080 pixel,700:1,400 cd
Display notes	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.	ISO 9241-307 - Pixel class II Viewing angle: Left/Right 89°, Top 89°, Bottom 89°; 30ms response time; Integrated ambient light sensor for automatic backlight adjustment to the working environment.
Sensors	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass	3-axis Accelerometer Gyroscope Ambient Light Sensor Magnetic Field Sensor Compass
Aspect ratio	16:9	16:9	16:9	16:9
Brightness - typical	400 cd	400 cd	400 cd	400 cd
Contrast - typical	700:1	700:1	700:1	700:1
Digitizer / Touch Technology	Dual Digitizer for pen input plus capacitive 10-finger multi-touch screen	Dual Digitizer for pen input plus capacitive 10-finger multi-touch screen	Dual Digitizer for pen input plus capacitive 10-finger multi-touch screen	Dual Digitizer for pen input plus capacitive 10-finger multi-touch screen
Ambient light sensor	Integrated	Integrated	Integrated	Integrated
Ambient light sensor notes	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight	While enabled, the ambient light sensor automatically adjusts the display backlight
Viewing angle (h/v) - typical	178°/178°	178°/178°	178°/178°	178°/178°
Graphics				
Base unit	STYLISTIC R726 i3/4GB/non-vPro	STYLISTIC R726 i5/4GB/non-vPro	STYLISTIC R726 i5/8GB/VPro	STYLISTIC R726 i7/8GB/VPro
TFT resolution (HDMI)	up to 4,096 × 2,160	up to 4,096 × 2,160	up to 4,096 × 2,160	up to 4,096 × 2,160
TFT resolution (VGA)	1,920 x 1,080 pixel	1,920 x 1,080 pixel	1,920 x 1,080 pixel	1,920 x 1,080 pixel
Max. resolution external display	4,096 x 2,304 pixel	4,096 x 2,304 pixel	4,096 x 2,304 pixel	4,096 x 2,304 pixel
Max. resolution display port	4,096 x 2,304 pixel	4,096 x 2,304 pixel	4,096 x 2,304 pixel	4,096 x 2,304 pixel
Graphics brand name	Intel® HD Graphics 520	Intel® HD Graphics 520	Intel® HD Graphics 520	Intel® HD Graphics 520
Graphics features	3 Display Support (2 external, 1 internal)	3 Display Support (2 external, 1 internal)	3 Display Support (2 external, 1 internal)	3 Display Support (2 external, 1 internal)
Graphics notes	Shared memory depending on main memory size and operating system	Shared memory depending on main memory size and operating system	Shared memory depending on main memory size and operating system	Shared memory depending on main memory size and operating system
Interfaces				
Audio: line-out / headphone	1 (combo port with Audio line-in)			
Audio: line-in / microphone	1 (combo port with Audio line-out)			
Internal microphones	2 (digital)			
USB 3.0 total	1 (Anytime USB-charge)			
VGA	1 (via optional cradle or optional conversion cable)			
mini DisplayPort	1			
HDMI	1 via optional cradle or optional DP conversion cable			
Ethernet (RJ-45)	1 (via optional cradle or optional conversion cable)			
Memory card slots	1 microSD up to 2GB, microSDHC up to 32GB, microSDXC up to 128GB Speed Class: up to UHS-I			
SIM card slot	1 (MicroSIM - only for models with integrated 3G/UMTS or 4G/LTE module)			
Interface Module notes	VGA and HDMI via conversion cables (mini DP to VGA and mini DP to HDMI), Ethernet via conversion cable (USB to RJ-45)			

Wireless technologies

Antennas	2x dual band for WLAN, 2x for UMTS/LTE, Bluetooth shared with WLAN, 1 x NFC
Bluetooth	Bluetooth 4.1 LE
WLAN notes	Import and usage according to country-specific regulations.
LTE/UMTS/GPS notes	Including GPS functionality Import and usage according to country-specific regulations.
NFC	optional
GPS	Embedded in 3G/4G module if configured with WWAN

Power supply

AC adapter	19 V / 65 W (3.42 A)
Rated voltage range	100 V - 240 V (AC Input)
Rated frequency range	50 Hz - 60 Hz
1st battery	Lithium polymer battery 4-cell, 34 Wh
Runtime 1st battery	up to 8h 52min / Productivity Workload MobileMark® 2014
Battery charging time	~ 3h
Battery notes	Battery runtime information is based on worldwide acknowledged BAPCo® MobileMark® 2014 (office productivity). Refer to www.bapco.com for additional details. The BAPCo® MobileMark® Benchmark provides results that enable direct product comparisons between manufacturers. It does not guarantee any specific battery runtime which actually can be lower and may vary depending on product model, configuration, application and power management settings. The battery capacity decreases slightly with every re-charge and over its lifetime.

Dimensions / Weight / Environmental

Dimensions (W x D x H)	319 x 9.5 x 201 mm 12.55 x 0.37 x 7.91 inch
Weight	from 830 g
Weight (lbs)	1.74 lbs
Weight notes	Weight may vary depending on actual configuration (including battery pack)
Operating ambient temperature	Running: 5 - 35 °C; Packed -15 - 60 °C
Operating relative humidity	Running: 20 - 85%; Packed 8 - 85% (relative humidity, non-condensing)
Product	STYLISTIC R726
Germany	GS (planned)
Europe	CE! EN 60950
Global	ENERGY STAR® 6.1 in progress EPEAT® Gold (dedicated regions) (planned) RoHS (Restriction of hazardous substances) WEEE (Waste electrical and electronic equipment) IT-Eco-Declaration Microsoft Operating Systems (HCT / HCL entry / WHQL)
Compliance link	http://globalsp.ts.fujitsu.com/sites/certificates

Additional Software

Additional software (preinstalled)	Adobe® Reader® (pdf reader) CyberLink YouCam (webcam software) Fujitsu DeskUpdate (Driver and Utility tool) ShockSensor Utility Power Saving Utility Fujitsu Plugfree Network (network management utility) EasyGuide online user documentation Microsoft Office (buy license to activate the pre-installed Microsoft Office)
Additional software (optional)	Drivers & Utilities DVD (DUDVD) Connection manager (optional with 4G/LTE or 3G/UMTS) DVD playback software CyberLink YouCam (webcam software) Recovery DVD for Windows®

Manageability

Manageability technology	PXE 2.1 Boot code Wake up from S5 (off mode) WoL (Wake on LAN)	PXE 2.1 Boot code Wake up from S5 (off mode) Intel® vPro™ technology WoL (Wake on LAN) iAMT 11.0 (depending on processor)
Supported standards	WMI PXE BootP (made4you)	

Security

System and BIOS Security	Absolute Persistence® technology capable BIOS Trusted Platform Module (TPM 2.0)	Absolute Persistence® technology capable BIOS Trusted Platform Module (TPM 2.0)	Absolute Persistence® technology capable BIOS Trusted Platform Module (TPM 2.0)	Absolute Persistence® technology capable BIOS Trusted Platform Module (TPM 2.0)
User Security	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)	Hard disk password User and supervisor BIOS password Workplace Protect (secure authentication solution)

Warranty

Warranty period	2 years (depending on country)
Warranty type	Collect & Return Service / Bring-in Service (for countries within region FTS CEMEA&I, for all other countries depending on local regulations)
Warranty Terms & Conditions	http://support.ts.fujitsu.com/warranty
Product Support Services - the perfect extension	
Recommended Service	9x5, Onsite Response Time: Next Business Day
Spare Parts availability	3 years (depending on country)
Service Weblink	http://ts.fujitsu.com/Supportservice

Recommended Accessories

Cradle STYLISTIC R726



The cradle for STYLISTIC R726 allows you switch from mobile to desktop productivity mode in one click. Enjoy a complete desktop experience with a FUJITSU display, wireless mouse and keyboard or magnetic keyboard and work comfortably on spreadsheets or presentations.

Order Code:
S26391-F2167-L100

Prestige Case Mini 13



The Prestige Case Mini 13 protects notebooks with up to 13-inch screens. The front half of the bag has dedicated compartments for your notebook, power cord, office supplies and personal items. The back half of the bag has an expanding, divided compartment for your files.

Order Code:
S26391-F1192-L151

Active Pen (incl. Battery)



The FUJITSU Active Pen (incl. battery) allows you to write naturally on your STYLISTIC R726 to let you take notes, fill form sheets or navigate the system.

Order Code:
S26391-F2169-L100

VGA conversion cable (miniDP to VGA)



The FUJITSU VGA Conversion Cable lets you connect your STYLITIC tablet to projectors and screens that have a VGA connector. (Picture similar to product)

Order Code:
S26391-F2169-L200

HDMI conversion cable (miniDP to HDMI)



The FUJITSU HDMI Conversion Cable lets you connect your STYLITIC tablet to projectors and screens that have a modern HDMI interface. (Picture similar to product)

Order Code:
S26391-F2169-L300

LAN conversion Cable (USB to LAN)



The FUJITSU LAN Conversion Cable allows you to connect your STYLITIC tablet to a wired network connection. (Picture similar to product)

Order Code:
S26391-F2169-L400

Notebook Mouse M410NB



The Notebook Mouse M410NB is the perfect optical notebook mouse for busy professionals on the road. It is compact enough that it easily slips into a notebook bag or briefcase without getting in the way. It features two buttons and a scroll wheel which can also be used as a third button.

Order Code:
S26381-K453-L100

External Super Multi Drive



For independent working and entertainment on your business or private trips, Fujitsu offers the small external DVD drive designed to travel with you. Upgrade your notebook or PC with this external drive and use it wherever you are.

Order Code:
S26341-F103-L135

Mobile Bluetooth Communication Speaker



The Fujitsu Mobile Bluetooth Communication Speaker is the perfect audio accessory for your connected mobile life. It is smaller than a tennis ball so you can bring it everywhere and it can connect via Bluetooth so you don't have to worry about cords. An integrated microphone gives you on-the-fly conference call capabilities for all your Bluetooth enabled mobile devices.

Order Code:
S26391-F7128-L700

UC&C USB Headset Stereo H650e



The UC&C USB Headset Stereo H650e is the ultimate in style and functionality. Long, uncomfortable work calls are a thing of the past thanks to the cushioned ear pads and crystal clear sound. Adjustable headband and microphone provides the perfect fit for everyone. Optimized for Microsoft® Lync™ the headset displays a red 'in-call' LED to let your co-workers know when you're available, thus helping to boost office productivity.

Order Code:
S26391-F7139-L10

Magnetic Keyboard STYLISTIC R726



The Magnetic Keyboard for the STYLITIC R726 empowers you to easily switch between tablet and notebook mode. Its magnetic connection makes it easy to attach or detach it from the tablet so you can transform the device the way you want and need it for your individual workstyle.

S26391-F2114-L** (**country specific version)

Wireless Keyboard Set LX901



The Wireless Keyboard LX901 is a top of the line desktop solution for lifestyle orientated customers, who want only the best for their desk. This superb keyboard set offers ambitious users more functions, security and better features than a conventional interface device. It even includes 2.4 GHz technology and 128 AES encryption for security.

S26381-K565-L4** (**: Country specific variation)

More information

Fujitsu OPTIMIZATION Services

In addition to FUJITSU Tablet STYLISTIC R726, Fujitsu provides a range of platform solutions. They combine reliable Fujitsu products with the best in services, know-how and worldwide partnerships.

Fujitsu Portfolio

Build on industry standards, Fujitsu offers a full portfolio of IT hardware and software products, services, solutions and cloud offering, ranging from clients to datacenter solutions and includes the broad stack of Business Solutions, as well as the full stack of Cloud offering. This allows customers to leverage from alternative sourcing and delivery models to increase their business agility and to improve their IT operation's reliability.

Computing Products

www.fujitsu.com/global/products/computing/

Software

www.fujitsu.com/software/

More information

Learn more about FUJITSU Tablet STYLISTIC R726, please contact your Fujitsu sales representative or Fujitsu Business partner, or visit our website.
www.fujitsu.com/ts/tablet

Fujitsu green policy innovation

Fujitsu Green Policy Innovation is our worldwide project for reducing burdens on the environment. Using our global know-how, we aim to contribute to the creation of a sustainable environment for future generations through IT. Please find further information at <http://www.fujitsu.com/global/about/environment>



Copyrights

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2016 Fujitsu Technology Solutions GmbH

Disclaimer

Technical data is subject to modification and delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner.

CONTACT

Fujitsu Technology Solutions GmbH
Website: www.fujitsu.com/fts
2016-01-25 CE-EN

All rights reserved, including intellectual property rights. Changes to technical data reserved. Delivery subject to availability. Any liability that the data and illustrations are complete, actual or correct is excluded. Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see www.fujitsu.com/terms
© 2016 Fujitsu Technology Solutions GmbH